

ProBlend 77

Define | Design | Develop | Deliver

ProBlend 77 from SWT group is a specially formulated bitumen-based high solids rust preventative which will provide years of underbody corrosion protection for all types of vehicles in any environment. This latest offering from SWT Groups' wide range of rust preventive products provides the additional benefit of superior chip resistance while minimizing road and powertrain noise incursion to the vehicle passenger compartment. **ProBlend 77** exhibits superior durability against road salts and most automotive chemicals while standing up well to power washer spray and extreme weather conditions.

Physical Properties (Typical)			
Colour	Black	Solids by volume	75 %
Odor	Mild solvent	Sag Resistance	>60 Mils
Flammability	Fire is self-extinguishing	Viscosity	15 000 – 25 000 (Typical)

Performance Data			
Test	Method	Specification	Result
Salt Spray	ASTM B117	3000 Hrs	<1%
Chip Resistance 10 Mil DFT @23°C	ASTM D3170	2-4 chips <1mm	8A
Chip Resistance 10 Mil DFT @ -20°C	ASTM D3170	2-4 Chips 1-3mm	8B
Dry Time	Air cure	Dry to touch	60 min

Surface Preparation

Surface should be dry and free of loose material and or other contaminants for optimal results.

Application

PROBLEND 77 can be sprayed on or brushed on with equal effectiveness.

The ratings and data contained herein are based on information obtained through controlled laboratory methods. We recommend that the customer determine the suitability of these materials before adopting them for its own use